

Performance monitoring commands	
estat clear	clear performance counters
estat describe <name> all	get description of one or all performance counters
estat print [-cont=<n>] [-dsigauges -dsitrans]	display performance counters
[-cont]	display all gauges and counters at regular intervals
[-dsigauges -dsitrans]	display gauges or counters at regular intervals

First-time initialization commands	
init	initialize Entrust/PKI
subordinate make-subcert-req	generate a PKCS #10 certificate request to be sent to a superior CA
subordinate read-subcert	import a PKCS #7 response from a superior CA into Entrust/Authority

Tcl syntax tips

Basic syntax: command arguments

- \ used to:
- keep commands and arguments together if they span more than one line
 - quote special characters
 - turn off meaning of symbols such as “”, { }, [], \$

“ ” group words into single argument

{ } group words into single argument; elements such as [] and \$ are not interpreted as Tcl syntax

Tcl resources

Practical Programming in Tcl and Tk Third Edition, Brent B. Welsh, Prentice Hall PTR
Graphical Applications with Tcl & Tk Second Edition, Eric Foster-Johnson, M&T Books
<http://www.scripts.com>
<http://www.beedub.com/book>

Additional documentation on Entrust Master Control Command Shell

See “Command-line interface for Entrust/Authority Master Control” in *Administering Entrust/PKI 6.0 on Windows* or *Administering Entrust/PKI 6.0 on UNIX*.

Entrust Master Control Command Shell

Quick Reference

Release 6.0.1 for Windows and UNIX

How to use this card

- < > indicate variables, for example, <subsys>
[] indicate options, for example, [-ldap]
| indicates either/or parameters, for example, all | list
+ indicates multiple values can be configured in one command

Security classes

- Commands with no key icon are non-harmful commands not requiring access to the database. Require no authorization.
- ! Non-harmful commands. Autologin must be enabled or you must be logged in to an active Entrust Master Control Command Shell session.
- !! Commands requiring access to the database but not causing irreversible change. You must be logged in to an active Entrust Master Control Command Shell session.
- !!! Commands causing a policy change or update that may be irreversible. Requires one additional Master User password if policy has been set to require multiple authorizations. Otherwise, command shell may issue warning and yes/no prompt.

Getting help	
help or ?	get list of all commands
help all list <cmd>	get help on all commands, list all commands, or get help on single command
apropos <regex>	find commands related to regular expression
util errinfo <code>	describe error code
version	show release information

Logging in and out	
login	log in to Entrust/Authority Master Control !
logout	log out of Entrust/Authority Master Control !
exit	stop the command shell
passwd <user>	change a Master User password !!!



Visit our Web site at www.entrust.com.

© 2000-2002 Entrust, Inc. All rights reserved.
Entrust is a registered trademark of Entrust, Inc. All Entrust product names are trademarks of Entrust, Inc. All other company and product names may be trademarks or registered trademarks of their respective owners.
This information is subject to change as Entrust, Inc. reserves the right to, without notice, make changes to its products as progress in engineering or manufacturing methods or circumstances may warrant.
Export and/or import of cryptographic products may be restricted by various regulations in various countries. Licenses may be required.
Published in Canada.
Release 6.0.1.

Entrust/Authority service commands		
service autologin query enable disable	query, enable, or disable automatic login	???
service config <subsys> query enable disable procs <n>	query, enable, or disable Entrust/Authority subsystem, or assign a number of processes to a subsystem	??
service start	start the service	?
service status	display the service status	??
service stop	stop the service	??
CA management commands		
ca cert config [-lifetime <value> -period <value>]+	change the lifetime and/or the private key usage period of the next CA certificate	???
	-lifetime set CA certificate lifetime (months)	
	-period set private key usage period (percent of CA certificate lifetime)	
ca cert export -binary -pem {-x509 -cert -pkcs7} -wtls [-overwrite] <file>	export a CA certificate to file	??
	-binary -pem export as binary or PEM	
	-x509 -wtls export as X.509 or WTLS certificate	
	-cert -pkcs7 if X.509, return CA certificate, or certificate chain including superior CAs if current CA is subordinate	
	[-overwrite] overwrite existing file	
	<file> specify filename	
ca cert get <sernum>	list detailed information about the CA certificate related to specified serial number	??
ca cert list	list all CA certificates	??
ca cert query	query CA certificate settings	??
ca cert revoke [-reason unspecified cacompromise superseded] [-text <value>] [-time [dd-mm[-yy[yy]].][hh:mm[:ss]]] <sernum>	revoke all CA and link certificates related to specified serial number	???
	[-reasonunspecified cacompromise superseded] specify reason for revocation	
	[-text] add a comment	
	[-time] specify time when certificate was last known to be uncompromised	
	<sernum> specify a certificate serial number	
ca key config -alg RSA-1024 RSA-2048 DSA-1024	set the key type and size for the next CA key that is generated	???
ca key ec-params load <file>	load CA key elliptic curve parameters	???
ca key ec-params set-named <curve name>	set CA key elliptic curve parameters to a named curve	???

ca key ec-params write [-force] <ini file>	write CA key elliptic curve parameters to an initialization file	???
	[-force] overwrite an existing initialization file	
	<ini file> pathname of initialization file	
ca key move	move existing CA key to cryptographic hardware	???
ca key query	return the key type and size for the next CA key that is generated	??
ca key update	generate new CA certificate for new signing private key; save to software or hardware	???
ca keyrecover-all	set all clients up for key recovery	???
ca resynch-next-cert-serial	reset the certificate serial number	??
recover ca	recover CA profile	??

Policy management commands		
policy authcode-dist enable disable query	enable, disable, or query authorization code distribution	???
policy auths enable disable query	enable, disable, or query Master User command authorization level	???
policy hasher md5 sha1 query	configure or query certificate hashing algorithm	???
policy proto-enc cast-80 cast-128 triple-des query	configure or query protocol encryption algorithm	???
policy user-enc-keylen 1024 2048 query	configure or query user encryption key length	???

Revocation list management commands		
offlineARLs	update offline ARLs before they expire (if enabled)	???
rl count -crl -arl	return a count of CRLs or ARLs	?
rl export [-pem -bin] [-fn <fn>] (-crl <#>) (-arl <#>) (-cert <sn>) -combined	return a CRL or ARL	?
	[-pem -bin] return as PEM or binary	
	[-fn] save the data to a file	
	-crl -arl -cert -combined specify CRL number, ARL number, certificate serial number, or combined CRL	

Directory management commands		
dsa diradmin <dn>	change the Directory Administrator DN	??
dsa passwd [-ldap] ca diradmin	change the CA Directory Access password or the Directory Administrator password	???
	[-ldap] change password both in Directory and Entrust	
	ca diradmin specify either CA or Directory Administrator password	
dsa pushrls	write CRLs and ARLs to Directory	??
dsa restore all ca	restore CA data or all certificates to Directory	??

Certificate definition file commands		
fcs export <file>	write certificate specifications from database to file	??
fcs import <file>	import specifications from certificate definition file into database	??

Security Officer commands		
officer auths query set <n>	get or change number of Security Officer authorizations required for sensitive operations	???
officer client-setting (query <name> all) (set <name> <value>)	get or set Security Officer client-side settings	???
officer create <dn>	create a Security Officer	???
officer list	list Security Officers	??
officer recover <dn>	recover a Security Officer	???

Database management commands		
db backup incremental full query config { -dir <backup-directory> -keep <n> -timer <incremental-period> <full-period> <notbefore> <notafter> }+	perform, query, or configure full or incremental data backup	?
	-dir set backup directory	
	-keep set number of backups to keep	
	-timer set backup schedule	
db get <var> all	get specific or all configuration variables	??
db hw-protection disable	remove hardware-based database protection	???
db hw-protection enable -alg DESITriple-DESICAST-128	protect the database with a hardware-based key	???
db hw-protection query	query hardware-based database protection	???
db integrity validate query config { -timer <period> <notbefore> <notafter> }	perform, query, or configure automatic database validation	?
	-timer set database validation schedule	
db lsaud [-d] [-f <outfile>] { <file>... [-s [dd-mm[-yy[yy]].]<hh:mm[:ss]> <day>] [-e date-time] }	list/check the audit file	?
	[-d] obtain complete description of activity	
	[-f] write audit logs to file	
	<file>... [-s] [-e] view audit logs sent to file or specify start and end time for the log view	
db re-encrypt	generate new random values for database encryption keys and re-encrypt database	???
db reports-timezone	update timezone information for reports	??
db set <var> <value>	set configuration variable	??